

# UP 35 | SSC

genuine and solid



Features

**Technical data**

20 kN Crimp Force | Pneumatic | Air pressure 6 bar | 87 PSI

**Process-safe**

Due to forced sequence control and with linear crimping movement, ideal for use in automotive and industrial applications

**Application range**

Uninsulated contacts up to 16 mm<sup>2</sup> | Insulated terminals up to 10 mm<sup>2</sup> | Wire end ferrules up to 50 mm<sup>2</sup> | Automotive connectors up to 10 mm<sup>2</sup>

**Different**

UP 35 BA with contact hold function, no hands in the working area due to additional lever (mountable for left and right-handed users), ideal for miniatur plugs < 0,14 mm<sup>2</sup>

**High-quality**

SSC with safety function - working without finger protection, operate contact hold function with double foot pedal, no hands in the working area

**Flexible**

React to different production orders with tool-free quick-change adapter system

**Portable**

25 kg weight, space saving design and portable to any place and immediately ready for use

**Reliable**

The production quantity is recorded by the electronic piece counter

**Individual**

Different adapters allow almost unlimited variability for individual customer solutions, use of external dies possible

**Varied**

A selection of standard processing solutions with and without positioning system available from stock

**User-friendly**

Safety or two-hand operation optionally available

**Customized**

Customized versions in design and function are available on request

**Reliable**

Quality Made in Germany and CE compliant

Versions

**Pneumatic Crimping Machine UP 35**

Linear working mechanism (standard version).

**Pneumatic Crimping Machine UP 35 | BA**

Linear working mechanism. With integrated contact holding system operated manually by hand lever.

**Pneumatic Crimping Machine SSC**

Linear working mechanism. Can be operated without finger guard and with double foot pedal.